



iDesigno

20W King Downlight

TECHNICAL DATA SHEET

A contemporary downlight designed to elevate any interior with its refined form and versatile mounting options. Available in a range of finishes and reflector styles, it can be surface mounted or suspended; adding a stylish focal point to commercial and architectural spaces.

Areas for Application

- Retail Stores
- Offices
- Showrooms
- Reception Areas
- Commercial Areas

8/94 Forsyth Street
O'Connor WA 6163
08 6371 1780
sales@ledtec.com.au
www.iDesigno.com.au
iDesigno is a brand by Ledtec



LEDTEC

TECHNICAL SPECIFICATIONS

Product	
Model - IP54 - 115mm	<i>ID-DLI-KING-20W-60-4K-115</i>
Model - IP65 - 170mm	<i>ID-DLI-KING-20W-60-4K-170</i>

Luminaire Information	
Rated Power	<i>20W</i>
Installation	<i>Surface Mounted</i>
Dimming Option	<i>Dimmable DALI Dimmable Optional</i>

Driver Information	
Driver Type	<i>Built In Flicker Free</i>
Dimming Option	<i>Non-Dimmable</i>
Rated Input Voltage	<i>AC 220 - 240V</i>


Warranty	
Warranty	<i>5 Years</i>

Material & Finish	
Ingress Protection Rating	<i>IP54 - 115 x 152mm IP65 - 170 x 182mm</i>
Material Composition (Housing)	<i>Aluminum</i>
Product Finish (Base)	<i>White Black</i>


Product Dimensions	
Dimensions	<i>IP54: 115 x 152mm IP65: 170 x 182mm</i>

Optical Characteristics	
Correlated Colour Temperature	<i>4000K Standard 2700K - 4000K Optional</i>
Colour Rendering Index	<i>90Ra</i>
LED Type	<i>Cree</i>
LED Expected Lifespan	<i>50,000hrs</i>
Luminous Flux	<i>1800 - 2000lms</i>
Beam Angle	<i>20° / 40° / 60°</i>
SDCM	<i><3</i>

SIZE DIAGRAMS



IP54 VERSION



IP65 VERSION