



iDesigno 4W Retico Downlight

TECHNICAL DATA SHEET

A functional grid light available in various configurations. Designed for modern commercial spaces, it delivers precise, low-glare illumination; ideal for highlighting architectural features or achieving balanced general lighting.

Areas for Application

- Offices & Boardrooms
- Retail & Shopping Centres
- Galleries & Display Areas
 - Hospitality Interiors
 - Receptions

8/94 Forsyth Street
O'Connor WA 6163
08 6371 1780
sales@ledtec.com.au
www.iDesigno.com.au
iDesigno is a brand by Ledtec



LEDTEC

TECHNICAL SPECIFICATIONS

Product		Material & Finish	
Model - White	<i>ID-DLI-RET-4W-4K-45-DIM</i>	Ingress Protection Rating	<i>IP20</i>
Luminaire Information		Material Composition (Housing)	<i>Aluminum</i>
Rated Power	<i>2 x 2W</i>	Product Finish (Base)	<i>White / Black</i>
Installation	<i>Recessed</i>	Product Dimensions	
Dimming Option	<i>Dimmable DALI Dimmable Optional</i>	Dimensions	<i>75 x 45 x 49mm</i>
Driver Information		Cut Out	<i>68 x 37mm</i>
Driver Type	<i>Built in Flicker Free</i>	Optical Characteristics	
Dimming Option	<i>Dimmable</i>	Correlated Colour Temperature	<i>4000K Standard 2700K - 4000K Optional</i>
Rated Input Voltage	<i>AC 220 - 240V</i>	Colour Rendering Index	<i>90Ra</i>
Warranty		LED Type	<i>Luminus</i>
Warranty	<i>5 Years</i>	LED Expected Lifespan	<i>50,000hrs</i>
		Luminous Flux	<i>240lms</i>
		Beam Angle	<i>15° / 30° / 45°</i>
		SDCM	<i><3</i>

SIZE DIAGRAMS

